



PALLET SYSTEM FOR MACHINING CENTERS



CE Package Available

AUTOMATIC PALLET SYSTEMS

- Unattended pallet change in seconds
- Up to 8000+ lbs. (3636 kgs.) Capacity
- Electric Servo Drive
- Dual Air Blast At Each Contact Pad
- Fully Integrated To Any CNC Machine By Only Two M Functions

MANUAL PALLET SYSTEMS

- Up to 2000 lbs (909 kgs.) capacity
- Linear Guide Rails
- Compact design includes telescoping legs, adapts to all machines including those with chip/coolant drawers
- Air Blast At Each Contact Pad
- Dual Palm Buttons (Series 20 and larger) For Maximum Safety



INCREASE MACHINE AND OPERATOR PRODUCTIVITY

- Exchange Fixtures In Seconds With +/- .0001" (.0025mm) Repeatability
- Load, Unload, Inspect Parts And Set Up Jobs While Alternate Pallet Is In Machine
- Tooling, Vises, Indexers, Or Any Workholding Device Can Be Dedicated Onto Inexpensive Pallets
- Pallets Easily Interchanged Between Machines Or Departments
- Palletized Jobs Easily Interrupted For Emergency Or J.I.T. Jobs
- Heavy/Large Workpieces Easily Loaded Outside The Machine

Since 1969, MIDACO has been a leader in providing innovative and quality solutions to improve manufacturing efficiency for companies worldwide.

At MIDACO, we're not only making state-of-the-art technology... We're making it affordable!

Engineered And Manufactured In The U.S.A.... Supported Throughout The World

AUTOMATIC PALLET SYSTEMS


STANDARD SYSTEM includes

- 1 Cast Iron Receiver with Airblast for Chip Removal
- 2 Plain Cast Aluminum Pallets
- 1 End Mounted Shuttle
- 1 Custom-Fitted, Automatic Door
- 1 High-Visibility Indicator Lamp
- 1 Pallet Clamp Confirmation

OPTIONS

- CE/CHIP Containment Enclosure
- Cast Iron, T-Slotted, Tapped-Hole Pallets
- Additional Models, Pallets and Pallet Transfer/Storage Accessories available

AUTOMATIC PALLET SYSTEMS



NOTE: Diagram Shows Optional CE Package.

NOTE: Diagram Shows Optional CE Package.

Automatic System

VMC Model	Travel	MIDACO Automatic #
VMC 2216	22" x 16"	A2416SD
VMC 3016	30" x 16"	A3016SD
VMC 3020	30" x 20"	A3020SD
VMC 800	31" x 20"	A3020SD
VMC 1000	40" x 20"	A4020SD
VMC 1024	40" x 24"	A4020SD or A4525SD
VMC 1500	60" x 30"	CONTACT MIDACO
VMC 2000	78" x 30"	CONTACT MIDACO

	SERIES 20SD	SERIES 30SD	SERIES 40SD	SERIES S5020SD	SERIES 5020/25SD	SERIES 60SD	SERIES 80SD
Clamping Force*	4500 (2043)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)	7500*** (3410)	15400 (7000)	15400 (7000)	20500 (9318)
Receiver Weight	136 (62)	350 (160)	350 (160)	350 (160)	450 (205)	450 (205)	2075 (942)
Pallet Weight	80 (36)	140 (64)	210 (95)	250 (113)	340 (155)	455 (207)	790 (359)
Pallet Thickness:	1.00 (25.4)	1.50 (38.1)	2.00 (50.8)	2.00 (50.8)	2.00 (50.8)	2.00 (50.8)	2.50 (63.5)
Pallet Load Cap:**	500 (227)	1000/2000*** (454/908)	1000/2000*** (454/908)	2000 (908)	4000 (1818)	4000 (1818)	8000 (3636)
A (Pallet X Dim)	24 (610)	30 (762)	40 (1016)	50 (1270)	50 (1270)	60 (1524)	80 (2032)
B (Pallet Y Dim)	12-15 (305-381)	15.5-19 (394-482)	15.5-19 (394-482)	15.5-19 (394-482)	19.5-24 (495-610)	19.5-29 (495-736)	25.5-30 (648-762)
C	5.85 (149)	6.35 (162)	6.85 (174)	6.85 (174)	6.85 (174)	6.85 (174)	9.13 (232)
D	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)	5.75 (146)
E	53 (1346)	58 (1473)	68 (1727)	78 (1980)	78 (1980)	88 (2235)	116 (2946)
F	40 (1016)	45 (1143)	45 (1143)	45 (1143)	57 (1448)	67 (1702)	73 (1854)
G (Max Height)	36.5 (927)	38 (965)	38 (965)	38 (965)	38 (965)	38 (965)	40 (1016)
H (Max Height)	44 (1118)	49 (1245)	49 (1245)	49 (1245)	52 (1321)	52 (1321)	60 (1524)
J (Receiver)	11.5 (292)	15.5 (394)	15.5 (394)	15.5 (394)	19.5 (495)	19.5 (495)	25.5 (648)
K (Receiver)	22 (559)	30 (762)	30 (762)	30 (762)	40 (1016)	40 (1016)	75 (1905)
L (Door Opening)	18 (457)	20 (508)	20 (508)	20 (508)	28 (711)	28 (711)	32 (813)
M (Optional Package)	20.8 (528)	20.8 (528)	20.8 (528)	20.8 (528)	20.8 (528)	20.8 (528)	21 (533)
N (Optional Package)	36.5 (927)	42 (1067)	51 (1295)	61 (1549)	61 (1549)	71 (1803)	91 (2311)

Automatic systems require 2 M functions and 230 volt, 3 phase, 30 amp electric service for installation.

MANUAL PALLET SYSTEMS


STANDARD MANUAL SYSTEM includes

- 1 Cast Iron Receiver with Air Blast for Chip Removal
- 2 Plain Cast Aluminum Pallets
- 1 Front-Mounted Side-By-Side Shuttle
- 1 Pallet Clamp Confirmation

OPTIONS

- Cast Iron, T-Slotted, Tapped-Hole Pallets
- Additional Models, Pallets and Pallet Transfer/Storage Accessories Available

MANUAL PALLET SYSTEMS



Manual System

VMC Model	Travel	MIDACO Manual #
VMC 2216	22" x 16"	M3016FL
VMC 3016	30" x 16"	M3016FL
VMC 3020	30" x 20"	M3020FL
VMC 800	31" x 20"	M3020FL
VMC 1000	40" x 20"	M4020FL
VMC 1024	40" x 24"	M4020FL*
VMC 1500	60" x 30"	M6030FL
VMC 2000	78" x 30"	M7230FL

* Larger Systems Available

	M1614FL	M2216FL	M2020FL	M3016/18/20FL	M4020FL	M5020FL	M5025/30FL	M6030FL	M7230FL
Clamping Force*	4200 (1905)	4200 (1905)	4200 (1905)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)
Receiver Weight	95 (43)	135 (61)	135 (61)	350 (160)	350 (160)	350 (160)	350 (160)	350 (160)	350 (160)
Pallet Weight	31 (14)	55 (25)	63 (29)	140 (64)	212 (96)	252 (115)	325 (148)	435 (198)	510 (232)
Pallet Thickness:	1.0 (25.4)	1.0 (25.4)	1.0 (25.4)	1.5 (38)	2.0 (50.8)	2.0 (50.8)	2.0 (50.8)	2.0 (50.8)	2.0 (50.8)
Pallet Load Cap:**	300 (136)	300 (136)	300 (136)	1000/2000*** (454/908)	1000/2000*** (454/908)	500/2000*** (227/908)	500/2000*** (227/908)	500/2000*** (227/908)	500/2000*** (227/908)
A (Pallet X Dim)	16 (406)	22 (559)	20 (508)	30 (762)	40 (1016)	50 (1270)	50 (1270)	50-60 (1270-1524)	72 (1829)
B (Pallet Y Dim)	14 (356)	16 (406)	20 (508)	16-20 (406-508)	20 (508)	20 (508)	25 (635)	30 (762)	30 (762)
C	4.12 (104)	4.12 (104)	4.12 (104)	6.35 (162)	6.85 (174)	6.85 (174)	6.85 (174)	6.85 (174)	6.85 (174)
D	80 (2032)	80 (2032)	80 (2032)	109 (2770)	138 (3505)	168 (4267)	168 (4267)	198 (5030)	234 (5944)
E	21.3 (541)	21.3 (541)	24.3 (541)	26 (660)	26 (660)	26 (660)	31 (787)	36 (914)	36 (914)
F (Min Height)	29 (736)	29 (736)	29 (736)	34.5 (876)	35 (889)	40 (1016)	40 (1016)	40 (1016)	40 (1016)
G (Max Height)	39 (990)	39 (990)	39 (990)	44 (1117)	45 (1143)	51 (1295)	51 (1295)	51 (1295)	54 (1372)
H	****	****	****	****	****	****	****	****	****
I	29 (736)	29 (736)	29 (736)	39 (990)	42 (1066)	52 (1321)	52 (1321)	62 (1575)	74 (1880)
J (Receiver)	14 (355)	19 (483)	19 (483)	30 (762)	30 (762)	30 (762)	30 (762)	30 (762)	30 (762)
K (Receiver)	13 (330)	13 (330)	13 (330)	15.5 (394)	15.5 (394)	15.5 (394)	15.5 (394)	15.5 (394)	15.5 (394)
L	2.5 (63.5)	2.5 (63.5)	2.5 (63.5)	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)
M	9.0 (229)	9.0 (229)	10 (254)	7.0 (178)	11 (275)	11 (275)	14 (356)	14 (356)	16 (406)

Weight capacities shown in lbs (kgs). Dimensions shown in inch (mm) *At 100PSI (6.9 bar) **At 120PSI (8.2 bar) ***Optional 2000 lb (909 kg) Pallet Load Capacity available ****Manufactured to fit specific VMC application Patent Pending Specifications subject to change without notice.

- Midaco pallet systems are designed for machines with stationary guarding. Some machines require options or customization. Additional pallet systems for traveling column or special applications available. Contact your sales representative to confirm model and specifications for all applications



MIDACO CORPORATION

2000 EAST TOUHY AVENUE
ELK GROVE VILLAGE, IL 60007 U.S.A.

PHONE: 847.593.8420

FAX: 847.593.8451

www.midaco-corp.com

