


# Colchester

## PALLET SYSTEM FOR MACHINING CENTERS



CE Package Available

### AUTOMATIC PALLET SYSTEMS

- Unattended pallet change in seconds
- Up to 8000+ lbs. (3636 kgs.) Capacity
- Electric Servo Drive
- Dual Air Blast At Each Contact Pad
- Fully Integrated To Any CNC Machine By Only Two M Functions

### MANUAL PALLET SYSTEMS

- Up to 2000 lbs (909 kgs.) capacity
- Linear Guide Rails
- Compact design includes telescoping legs, adapts to all machines including those with chip/coolant drawers
- Air Blast At Each Contact Pad
- Dual Palm Buttons (Series 20 and larger) For Maximum Safety



### INCREASE MACHINE AND OPERATOR PRODUCTIVITY

- Exchange Fixtures In Seconds With +/- .0001" (.0025mm) Repeatability
- Load, Unload, Inspect Parts And Set Up Jobs While Alternate Pallet Is In Machine
- Tooling, Vises, Indexers, Or Any Workholding Device Can Be Dedicated Onto Inexpensive Pallets
- Pallets Easily Interchanged Between Machines Or Departments
- Palletized Jobs Easily Interrupted For Emergency Or J.I.T. Jobs
- Heavy/Large Workpieces Easily Loaded Outside The Machine

Since 1969, MIDACO has been a leader in providing innovative and quality solutions to improve manufacturing efficiency for companies worldwide.

*At MIDACO, we're not only making state-of-the-art technology... We're making it affordable!*

Engineered And Manufactured In The U.S.A.... Supported Throughout The World

# Colchester

## AUTOMATIC PALLET SYSTEMS


### STANDARD SYSTEM includes

- 1 Cast Iron Receiver with Airblast for Chip Removal
- 2 Plain Cast Aluminum Pallets
- 1 End Mounted Shuttle
- 1 Custom-Fitted, Automatic Door
- 1 High-Visibility Indicator Lamp
- 1 Pallet Clamp Confirmation

### OPTIONS

- CE/CHIP Containment Enclosure
- Cast Iron, T-Slotted, Tapped-Hole Pallets
- Additional Models, Pallets and Pallet Transfer/Storage Accessories available

## AUTOMATIC PALLET SYSTEMS



### Automatic System

VMC Model	Travel	MIDACO Automatic #
SV-600	27" x 16"	A2416SD
SV-1000	40" x 20"	A4020SD

	SERIES 20SD	SERIES 30SD	SERIES 40SD	SERIES S5020SD	SERIES 5020/25SD	SERIES 60SD	SERIES 80SD
Clamping Force*	4500 (2043)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)	7500*** (3410)	15400 (7000)	15400 (7000)	20500 (9318)
Receiver Weight	136 (62)	350 (160)	350 (160)	350 (160)	450 (205)	450 (205)	2075 (942)
Pallet Weight	80 (36)	140 (64)	210 (95)	250 (113)	340 (155)	455 (207)	790 (359)
Pallet Thickness:	1.00 (25.4)	1.50 (38.1)	2.00 (50.8)	2.00 (50.8)	2.00 (50.8)	2.00 (50.8)	2.50 (63.5)
Pallet Load Cap:**	500 (227)	1000/2000*** (454/908)	1000/2000*** (454/908)	2000 (908)	4000 (1818)	4000 (1818)	8000 (3636)
A (Pallet X Dim)	24 (610)	30 (762)	40 (1016)	50 (1270)	50 (1270)	60 (1524)	80 (2032)
B (Pallet Y Dim)	12-15 (305-381)	15.5-19 (394-482)	15.5-19 (394-482)	15.5-19 (394-482)	19.5-24 (495-610)	19.5-29 (495-736)	25.5-30 (648-762)
C	5.85 (149)	6.35 (162)	6.85 (174)	6.85 (174)	6.85 (174)	6.85 (174)	9.13 (232)
D	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)	5.75 (146)
E	53 (1346)	58 (1473)	68 (1727)	78 (1980)	78 (1980)	88 (2235)	116 (2946)
F	40 (1016)	45 (1143)	45 (1143)	45 (1143)	57 (1448)	67 (1702)	73 (1854)
G (Max Height)	36.5 (927)	38 (965)	38 (965)	38 (965)	38 (965)	38 (965)	40 (1016)
H (Max Height)	44 (1118)	49 (1245)	49 (1245)	49 (1245)	52 (1321)	52 (1321)	60 (1524)
J (Receiver)	11.5 (292)	15.5 (394)	15.5 (394)	15.5 (394)	19.5 (495)	19.5 (495)	25.5 (648)
K (Receiver)	22 (559)	30 (762)	30 (762)	30 (762)	40 (1016)	40 (1016)	75 (1905)
L (Door Opening)	18 (457)	20 (508)	20 (508)	20 (508)	28 (711)	28 (711)	32 (813)
M (Optional Package)	20.8 (528)	20.8 (528)	20.8 (528)	20.8 (528)	20.8 (528)	20.8 (528)	21 (533)
N (Optional Package)	36.5 (927)	42 (1067)	51 (1295)	61 (1549)	61 (1549)	71 (1803)	91 (2311)

Automatic systems require 2 M functions and 230 volt, 3 phase, 30 amp electric service for installation.

## MANUAL PALLET SYSTEMS


### STANDARD MANUAL SYSTEM includes

- 1 Cast Iron Receiver with Air Blast for Chip Removal
- 2 Plain Cast Aluminum Pallets
- 1 Front-Mounted Side-By-Side Shuttle
- 1 Pallet Clamp Confirmation

### OPTIONS

- Cast Iron, T-Slotted, Tapped-Hole Pallets
- Additional Models, Pallets and Pallet Transfer/Storage Accessories Available

## MANUAL PALLET SYSTEMS



### Manual System

VMC Model	Travel	MIDACO Manual #
SV-600	27" x 16"	M2216FL
SV-1000	40" x 20"	M4020FL

	M1614FL	M2216FL	M2020FL	M3016/18/20FL	M4020FL	M5020FL	M5025/30FL	M6030FL	M7230FL
Clamping Force*	4200 (1905)	4200 (1905)	4200 (1905)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)	5200/7500*** (2360/3410)
Receiver Weight	95 (43)	135 (61)	135 (61)	350 (160)	350 (160)	350 (160)	350 (160)	350 (160)	350 (160)
Pallet Weight	31 (14)	55 (25)	63 (29)	140 (64)	212 (96)	252 (115)	325 (148)	435 (198)	510 (232)
Pallet Thickness:	1.0 (25.4)	1.0 (25.4)	1.0 (25.4)	1.5 (38)	2.0 (50.8)	2.0 (50.8)	2.0 (50.8)	2.0 (50.8)	2.0 (50.8)
Pallet Load Cap:**	300 (136)	300 (136)	300 (136)	1000/2000*** (454/908)	1000/2000*** (454/908)	500/2000*** (227/908)	500/2000*** (227/908)	500/2000*** (227/908)	500/2000*** (227/908)
A (Pallet X Dim)	16 (406)	22 (559)	20 (508)	30 (762)	40 (1016)	50 (1270)	50 (1270)	50-60 (1270-1524)	72 (1829)
B (Pallet Y Dim)	14 (356)	16 (406)	20 (508)	16-20 (406-508)	20 (508)	20 (508)	25 (635)	30 (762)	30 (762)
C	4.12 (104)	4.12 (104)	4.12 (104)	6.35 (162)	6.85 (174)	6.85 (174)	6.85 (174)	6.85 (174)	6.85 (174)
D	80 (2032)	80 (2032)	80 (2032)	109 (2770)	138 (3505)	168 (4267)	168 (4267)	198 (5030)	234 (5944)
E	21.3 (541)	21.3 (541)	24.3 (541)	26 (660)	26 (660)	26 (660)	31 (787)	36 (914)	36 (914)
F (Min Height)	29 (736)	29 (736)	29 (736)	34.5 (876)	35 (889)	40 (1016)	40 (1016)	40 (1016)	40 (1016)
G (Max Height)	39 (990)	39 (990)	39 (990)	44 (1117)	45 (1143)	51 (1295)	51 (1295)	51 (1295)	54 (1372)
H	****	****	****	****	****	****	****	****	****
I	29 (736)	29 (736)	29 (736)	39 (990)	42 (1066)	52 (1321)	52 (1321)	62 (1575)	74 (1880)
J (Receiver)	14 (355)	19 (483)	19 (483)	30 (762)	30 (762)	30 (762)	30 (762)	30 (762)	30 (762)
K (Receiver)	13 (330)	13 (330)	13 (330)	15.5 (394)	15.5 (394)	15.5 (394)	15.5 (394)	15.5 (394)	15.5 (394)
L	2.5 (63.5)	2.5 (63.5)	2.5 (63.5)	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)	3.75 (95)
M	9.0 (229)	9.0 (229)	10 (254)	7.0 (178)	11 (275)	11 (275)	14 (356)	14 (356)	16 (406)

Weight capacities shown in lbs (kgs). Dimensions shown in inch (mm) \*At 100PSI (6.9 bar) \*\*At 120PSI (8.2 bar) \*\*\*Optional 2000 lb (909 kg) Pallet Load Capacity available \*\*\*\*Manufactured to fit specific VMC application Patent Pending Specifications subject to change without notice.

- Midaco pallet systems are designed for machines with stationary guarding. Some machines require options or customization. Additional pallet systems for traveling column or special applications available. Contact your sales representative to confirm model and specifications for all applications



### MIDACO CORPORATION

2000 EAST TOUHY AVENUE  
ELK GROVE VILLAGE, IL 60007 U.S.A.

PHONE: 847.593.8420

FAX: 847.593.8451

www.midaco-corp.com



9-00